



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>C09D 10/00, 11/16</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 97/31070</b> <b>(43) International Publication Date:</b> 28 August 1997 (28.08.97)
<b>(21) International Application Number:</b> PCT/US97/03051 <b>(22) International Filing Date:</b> 21 February 1997 (21.02.97) <b>(30) Priority Data:</b> 08/605,725                      22 February 1996 (22.02.96)                      US 08/629,096                      8 April 1996 (08.04.96)                      US <b>(60) Parent Application or Grant</b> (63) Related by Continuation US    08/629,096 (CON) Filed on    8 April 1996 (08.04.96) <b>(71) Applicant (for all designated States except US):</b> THE GILLETTE COMPANY [US/US]; Prudential Tower Building, Boston, MA 02199 (US). <b>(72) Inventor; and</b> <b>(75) Inventor/Applicant (for US only):</b> WANG, Yichun [US/US]; 2 Robert Cohen Drive, Canton, MA 02021 (US). <b>(74) Agents:</b> HANDELMAN, Joseph, H. et al.; Ladas & Parry, 26 West 61st Street, New York, NY 10023 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>
<b>(54) Title:</b> INK ERADICATOR SYSTEM  <b>(57) Abstract</b>  An ink/eradicator fluid combination includes an ink containing a dye and a binding agent, and an eradicator fluid containing a basic nitrogen compound. The binding agent is capable of binding to the basic nitrogen compound.		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

- 1 -

INK ERADICATOR SYSTEM

This invention relates to ink eradicator systems.

Ink eradicator systems generally include two components. One component is an aqueous ink that includes a dye -- typically a triaryl methane -- that can be converted to a colorless form when contacted with a substance such as a sulfite reducing agent or a basic nitrogen compound. The second component is an aqueous eradicator fluid that includes a substance that can cause the dye to convert to a colorless form. A user writes with the ink and, if correction is necessary, applies the eradicator fluid to the ink marking to decolorize the dye.

It is desirable to be able to write-over the area to which an eradicator fluid is applied. One problem that may occur when write-over of an eradicated mark is attempted is that the new mark may fade over time as the dye in the ink comes into contact with the excess eradicating substance (e.g., sulfite or amine) in the hardened eradicator fluid.

The invention concerns the combination of an eradicatable ink aqueous ink and an aqueous eradicator fluid. The ink contains a dye that decolorizes if contacted with a basic nitrogen compound, such as an amine. The eradicator fluid contains the basic nitrogen compound. Importantly, the ink also includes a basic nitrogen compound binding agent that can bind the excess basic nitrogen compound in the eradicator

- 2 -

fluid. As a result, when the ink is used to overwrite an area to which the eradicator fluid has been applied, the remaining basic nitrogen compound in the eradicator fluid becomes bound to the nitrogen compound binding agent in the ink, and accordingly does not cause significant decolorization of the dye. The ink mark made over the eradicated area thus has a reduced tendency to fade over time.

The preferred dyes are triaryl methanes. The preferred basic nitrogen compounds are non-volatile, non-toxic amines like sodium glycinate. The preferred binding agents are metal salts. Magnesium salts like magnesium sulfate and zinc salts like zinc sulfate are examples of preferred binding agents.

Preferred eradicator fluids also include a film-forming polymer. The film-forming polymer provides a thin film on the eradicated area, and as a result may decrease the write-over time. It also may slow the diffusion of the eradicator fluid to the paper, and may improve write-over quality. Preferred film-forming polymers include polyacrylic acid sodium salts.

Preferred eradicator fluids have an eradication time of less than about 3 seconds, and more preferably less than 2 seconds. Preferred eradicator fluids have a write-over time of less than about 15 seconds and more preferably less than 10 seconds.

The invention also features an eradicatable ink including a dye that decolorizes when the ink is contacted with an 8% weight in water sodium glycinate solution, and a metal salt capable of complexing with sodium glycinate.

The invention also features a method of eradicating an ink marking on a substrate. The method includes two steps. First, an ink containing a dye that decolorizes if contacted with a basic nitrogen compound, a binding agent capable of binding the basic

- 3 -

nitrogen compound, and water is applied to the substrate to provide a marking. Second, an eradicator fluid including the basic nitrogen compound and water is applied to the marking. The basic nitrogen compound causes the dye to decolorize.

The invention also features another method of providing a marking. This method also includes two steps. First, an eradicator fluid containing a basic nitrogen compound and water is applied to a substrate to provide an eradicator fluid coating. Second, an ink containing a dye that decolorizes if contacted with the basic nitrogen compound, a binding agent capable of binding to the basic nitrogen compound, and water, is applied to the eradicator fluid coating. Preferably, the method also includes initially making a mark on the substrate, over which the eradicator fluid is applied, with the same ink.

"Eradication system", as used herein, means that an ink and an eradicator fluid combination are stored unmixed in the same general packaging. For example, the ink can be in one container and the eradicator fluid in a second container, but the two containers are included in the same package.

Other features and advantages of the invention will be apparent from the description of the preferred embodiments thereof, and from the claims.

Preferred combinations include an ink and an eradicator fluid. The ink contains a triaryl methane dye, a metal salt capable of binding to the amine used in the eradicator fluid, an organic acid, a polyacrylate film-forming polymer, and water. The eradicator fluid includes a non-volatile amine capable of decolorizing the triaryl methane dye, a film-forming polymer, and water. The ink and the eradicator fluid also may include a surfactant to adjust surface tension.

Triaryl methane dyes that are capable of

- 4 -

decolorizing in the presence of an amine are known to those skilled in the art. Examples include Acid Blue 93 and Acid Blue 22. Enough dye should be included in the ink to provide the desired color intensity, but not  
5 so much that large quantities of eradicator fluid must be applied to a mark made with the ink to cause it to decolorize. Preferred inks include between 2% and 5%, and more preferably approximately 4%, of the triaryl methane dye by weight.

10           The preferred metal salts are capable of binding to the amine used in the eradicator fluid. The metal salt preferably also is soluble in the ink. Examples of salts are magnesium sulfate and zinc sulfate.

15           The ink should include a quantity of metal salt sufficient to bind to excess amine when the ink is applied to an eradicator fluid layer made over an ink mark. But not so much metal salt should be included that excessive quantities of eradicator fluid must be  
20 applied to eradicate the ink mark being corrected. The ink mark to be corrected may include the metal salt, and enough amine must be in the eradicator fluid both to bind with the metal salt in the ink mark and to decolorize the dye. Preferred inks include between 5%  
25 and 15%, and more preferably between 8% and 12%, of the metal salt by weight.

          The organic acid increases the acidity of the ink and as a result increases the color intensity of the triaryl methane dye. Examples of organic acids  
30 include citric acid, and tartaric acid. A sufficient quantity of the organic acid should be included to provide an ink including a dye of the desired intensity. Preferred inks may include between 1% and 3%, and more preferably approximately 2%, of the  
35 organic acid by weight.

          The polyacrylate film-forming polymer can improve the color intensity and reduce feathering from

- 5 -

write-over. Examples of polyacrylate film-forming polymers include Sokalan CP10s, CP12s, and PA13PN, all of which are available from BASF. Enough polyacrylate film-forming polymer should be included in the ink to provide the targeted benefit, but not so much should be included that the viscosity of the ink becomes undesirably high. Preferred inks may include between 1% and 5%, and more preferably between 2% and 4%, of the polyacrylate film-forming polymer by weight.

Enough water should be included in the ink to dissolve the components and provide the ink with the desired viscosity. Preferred inks may have a viscosity between 1 cps and 3 cps, and more preferably between 2 cps and 2.5 cps. Preferred inks may include between 75% and 85% water by weight.

The non-volatile amine in the eradicator fluid causes the triaryl methane dye to decolorize when the fluid is applied over a mark made with the ink. The amine selected, in addition to preferably being non-volatile, should be non-toxic, and preferably odorless. Examples of preferred amines include glycine (in the form of sodium glycinate), other amino acid salts and polyamines.

Enough amine is included in the eradicator fluid to decolorize the dye when applied in reasonable quantities to a mark made with the ink. But large quantities of amine may interfere with the ability of the metal salt in the ink to sufficiently prohibit fading of a corrective ink marking applied to the hardened eradicator fluid. Preferred eradicator fluids may include between 7% and 12%, and more preferably between 8% and 10%, of the amine by weight.

The film-forming polymer increases the viscosity of the eradicator fluid. It also may decrease writeover time by providing a thin film on the surface of a covering made with the eradicator fluid; the thin film increases the hardness of the surface,

- 6 -

and may make the surface suitable to receive a mark made with ink even though the eradicator fluid has not fully dried. The film-forming polymer should be compatible with the amine used in the eradicator fluid.

5 Preferred film-forming polymers are sodium salts of polyacrylic acids. Preferred polyacrylic acid film-forming polymers have a number average molecular weight of between 1200 and 5000.

10 A sufficient quantity of the film-forming polymer is included in the eradicator fluid to provide the desired film and viscosity. Too much film-forming polymer may raise the viscosity to undesirable levels. Preferred eradicator fluids may include between 15% and 25%, and more preferably approximately 20%, of the  
15 film-forming polymer by weight.

Enough water should be included in the eradicator fluid to dissolve the components and provide the fluid with the desired viscosity. Preferred eradicator fluids may have, for example, a viscosity  
20 between 5 cps and 15 cps, and more preferably between 6 cps and 7 cps.

The eradicator fluid also preferably contains a buffer to maintain the pH of the solution at, for example, between 11 and 12 (more preferably at  
25 approximately 11.7). Preferred eradicator fluids may include, for example, between 75% and 85% of the aqueous buffer solution by weight.

The surface tension of the ink and the eradicator fluid can impact the eradication and  
30 writeover performance of the eradicator system. The surface tension of the ink preferably is between 30 dynes/cm and 45 dynes/cm, and more preferably is approximately 40 dynes/cm. The surface tension of the eradicator fluid preferably is between 20 dynes/cm and  
35 40 dynes/cm, more preferably is between 25 dynes/cm and 35 dynes/cm, and most preferably is approximately 30 dynes/cm. The surface tension of the ink and



- 7 -

eradicator fluid may be adjusted using conventional surfactants. If the surface tension of the ink is too low, the ink may penetrate too far into a paper substrate too quickly relative to the eradicator fluid that subsequently is applied. If the surface tension of the eradicator fluid is too high it may not penetrate into the paper as far, or at least as quickly, as the previously applied ink. This could lead to either incomplete eradication or an extended eradication time.

Other conventional ingredients such as bactericides, thickeners, and colorants can be included in the ink or the eradicator fluid.

The preferred inks and eradicator fluids can be used in roller ball point pens, e.g., pens which include a tubular member for fluid communication with a reservoir (either a fiber or hollow reservoir); a socket, having a seat, at one end of the member, an interior wall surface extending from the seat; a rim disposed at the end of the interior wall surface opposite the seat; and a spherical ball that is disposed in the socket, rotatably engagable with the seat and captured by the rim. The writing instrument may also include, for example, a felt tip. The inks and eradicator fluids may also be used in fountain pens.

In one embodiment, the ink and the eradicator fluid are supplied in separate pens. If desired, several ink containing pens may be provided, each pen containing an ink.

In another embodiment, the ink and the eradicator fluid are supplied in a single pen, containing a reservoir for each. Each reservoir may be either a hollow or fiber reservoir. The two reservoirs are surrounded by a tubular member, e.g., a polypropylene barrel. If the pen is a marker, it includes nibs at opposite ends, each nib being covered by a cap. An example of a suitable nib is the

- 8 -

polyethylene chisel nib available from Interflo. Alternatively, if it is a roller ball point pen it includes a ball and socket structure, as described above and as is well known in the art, at each end.

5 The ink reservoir may be large enough, for example, to include approximately three times as much fluid as the eradicator fluid reservoir.

The inks and eradicator fluids may be prepared by mixing the components.

10 Example 1

An ink was prepared by mixing 4 parts Acid Blue 93 (available from Orient), 2 parts citric acid, 10 parts magnesium sulfate, 2.5 parts Sokalan CP10s (available from BASF) and 81.5 parts water.

15 An eradicator fluid was prepared by mixing 10 parts sodium glycinate, 20 parts polyacrylic acid sodium salt (cat. no. 42034-4, available from Aldrich), 0.2 parts surfactant (Dynol, available from Air Products) and 70 parts of an aqueous buffer solution  
20 (pH 11.7). One liter of the buffer solution included 1.4841 g of boric acid, 4.1050 g of sodium hydroxide, 1.4 ml of acetic acid, and 1.4 ml of phosphoric acid.

The ink was used to write on Ampad note paper (available, for example, from Phase One Office Products  
25 Co., cat. no. AMP-20-372). The eradicator fluid was applied over a portion of the ink mark. After the eradicator fluid had hardened sufficiently, corrective ink marking was applied. No fading or feathering of the corrective marking was observed.

30 Example 2

An eradicator fluid was prepared by mixing 10% (by total weight) zinc sulfate, 2.5% Sokalan CP10s, 21 citric acid, 41 Acid Blue 93, and 81.51 water.

Example 3

35 An eradicator fluid was prepared by mixing 5% (by total weight) zinc sulfate, 5% magnesium sulfate, 2.5% Sokalan CP10s, 2% citric acid, 4% Acid Blue 93,

- 9 -

and 81.5% water.

Other embodiments are within the claims. For example, an eradicator fluid can be used in combination with two inks, one including a metal salt that binds  
5 the amine in the eradicator fluid, the other lacking the metal salt. An ink mark can be made on paper with the ink lacking the metal salt, and the eradicator fluid applied to decolorize the dye. A corrective marking then can be made with the ink including the  
10 metal salt.

- 10 -

C L A I M S

1. An ink and eradicator fluid combination,  
comprising  
an eradicator fluid containing a basic  
5 nitrogen compound and water, and  
an ink containing a dye that decolorizes if  
contacted with said basic nitrogen compound, a binding  
agent capable of binding said basic nitrogen compound,  
and water.
- 10 2. The combination of claim 1, wherein said  
eradicator fluid further includes a film-forming  
polymer.
3. The combination of claim 2, wherein said  
film-forming polymer comprises a polyacrylic acid salt.
- 15 4. The combination of claim 2, wherein said  
eradicator fluid contains between 8% and 10% of said  
basic nitrogen compound by weight, between 15% and 25%  
of said film-forming polymer by weight, and between 60%  
and 70% water by weight.
- 20 5. The combination of claim 1, wherein said ink  
further includes a film-forming polymer.
6. The combination of claim 1, wherein said ink  
contains between 3% and 4% of said dye by weight,  
between 8% and 12% of said binding agent by weight, and  
25 between 75% and 85% water by weight.
7. The combination of claim 5, wherein said  
film-forming polymer comprises a polyacrylate.
8. The combination of claim 7, wherein the pH of  
said eradicator fluid is between about 10 and about 11.
- 30 9. The combination of claim 1, wherein said dye  
comprises a triaryl methane.
10. The combination of claim 1, wherein said ink  
further comprises an organic acid.
11. The combination of claim 1, wherein said  
35 binding agent comprises a metal salt.
12. The combination of claim 11, wherein said  
metal salt comprise a magnesium salt.

- 11 -

13. The combination of claim 12, wherein said magnesium salt comprises magnesium sulfate.
14. The combination of claim 11, wherein said metal salt comprises a zinc salt.
- 5 15. The combination of claim 14, wherein said zinc salt comprises zinc sulfate.
16. The combination of claim 1, wherein said basic nitrogen compound comprises an amine.
- 10 17. The combination of claim 16, wherein said amine comprises sodium glycinate.
18. The combination of claim 1, wherein said eradicator fluid has an eradication time of less than 3 seconds.
- 15 19. The combination of claim 1, wherein said eradicator fluid has a write-over time of less than 10 seconds.
20. The combination of claim 1, wherein said ink has a surface tension of between 25 dynes/cm and 35 dynes/cm, and said eradicator fluid has a surface tension of between 35 dynes/cm and 40 dynes/cm.
- 20 21. An eradicatable ink, comprising a dye that decolorizes when said ink is contacted with an 8% by weight in water sodium glycinate solution, a metal salt capable of complexing with sodium glycinate, and water.
- 25 22. The eradicatable ink of claim 21, wherein said ink further comprises a non-volatile organic acid.
23. The eradicatable ink of claim 21, wherein said metal salt comprises a salt selected from the group consisting of magnesium salts and zinc salts.
- 30 24. A method of eradicating an ink marking on a substrate, comprising  
applying to said substrate an ink comprising  
a dye that decolorizes if contacted with a basic  
nitrogen compound, a binding agent capable of binding  
35 said basic nitrogen compound, and water, to provide a marking on said substrate, and  
applying to said marking an eradicator fluid

- 12 -

comprising said basic nitrogen compound and water, said basic nitrogen compound causing said dye to decolorize.

25. The method of claim 24, wherein said binding agent comprises a metal salt.

5 26. The method of claim 24, wherein said basic nitrogen compound comprises an amine.

27. A method of providing a marking, comprising  
applying an eradicator fluid containing a  
basic nitrogen compound and water to a substrate to  
10 provide an eradicator fluid coating on said substrate,  
and

applying to said eradicator fluid coating an  
ink containing a dye that decolorizes if contacted with  
said basic nitrogen compound, a binding agent capable  
15 of binding to said basic nitrogen compound, and water.

## INTERNATIONAL SEARCH REPORT

 International Application No  
 PCT/US 97/03051

 A. CLASSIFICATION OF SUBJECT MATTER  
 IPC 6 C09D10/00 C09D11/16

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)  
 IPC 6 C09D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 032 652 A (PELIKAN) 29 July 1981  see abstract ---	1,2, 9-11,14, 16,24-27
Y	EP 0 032 653 A (PELIKAN) 29 July 1981  see abstract ---	1,2, 9-11,14, 16,24-27
A	US 4 252 845 A (KENNETH G. GRIFFITHS) 24 February 1981 see abstract ---	1,24
A	DE 34 09 498 A (PELIKAN) 8 November 1984 see abstract -----	1,24

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

10 June 1997

Date of mailing of the international search report

25.06.97

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax (+31-70) 340-3016

Authorized officer

Girard, Y

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 97/03051

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 32652 A	29-07-81	NONE	
EP 32653 A	29-07-81	DE 3017601 A	12-11-81
US 4252845 A	24-02-81	NONE	
DE 3409498 A	08-11-84	NONE	